


LED15 SMD GU10


LED lamp / LED Lampe



LED15 SMD GU10



light distribution / Lichtverteilung
 $\Delta = 120^\circ$



E(0°) - max intensity in beam axis /
 maximale Stärke an der Strahlachse

Kanlux		
LED15 SMD GU10-WW	08940	2900-3500
LED15 SMD GU10-CW	08941	6200-6800

220-240V~	50/60Hz	2,5	2,5 - 22	15 LED SMD	GU10	210	120	≥ 80	20000	A		1/10/100	52	
-----------	---------	-----	----------	------------	------	-----	-----	-----------	-------	---	--	----------	----	--


light source uses SMD 5050 LEDs / das Leuchtmittel verfügt über SMD 5050 LED Dioden

LED24 SMD GU10

LED lamp / LED Lampe



LED24 SMD GU10



Kanlux				
NEW LED24 SMD GU10-WW	18471	3 - 26	2700-3200	270
NEW LED24 SMD GU10-CW	18470	3 - 28	5700-6300	300

220-240V~	50/60Hz	3	24 LED SMD	GU10	120	≥ 75	30000	>15000	A		1/10/100	55	
-----------	---------	---	------------	------	-----	-----------	-------	--------	---	--	----------	----	--


light source uses SMD 5050 LEDs / das Leuchtmittel verfügt über SMD 5050 LED Dioden

LED15 SMD MR16


LED lamp / LED Lampe



LED15 SMD MR16



light distribution / Lichtverteilung
 $\Delta = 120^\circ$



E(0°) - max intensity in beam axis / maximale Stärke an der Strahlachse

Kanlux	Kanlux	Tc [K]
LED15 SMD MR16-WW	08942	2900-3500
LED15 SMD MR16-CW	08943	6200-6800

12V DC, 2,5W, 2,5-22V, 15 LED SMD, Gx5,3, 210lm, 120°, Ra ≥ 80, 20000h, A+, 1/10/100, 40g, CE


light source uses SMD 5050 LEDs / das Leuchtmittel verfügt über SMD 5050 LED Dioden

LED24 SMD MR16

LED lamp / LED Lampe



LED24 SMD MR16



	Kanlux	Kanlux	(W)	Tc [K]	[lm]
NEW	LED24 SMD MR16-WW	18473	3 - 26	2700-3200	270
NEW	LED24 SMD MR16-CW	18472	3 - 28	5700-6300	300

12V AC/DC, 3W, 24 LED SMD, Gx5,3, 120°, Ra ≥ 75, 30000h, >15000lm, A+, 1/10/100, 40g, CE

light source uses SMD 5050 LEDs / das Leuchtmittel verfügt über SMD 5050 LED Dioden

LED15 SMD E14 / E27


LED lamp / LED Lampe



LED15 SMD E14




LED15 SMD E27



Kanlux	Kanlux	LED	Tc [K]	[g]
LED15 SMD E14-WW	08944	E14	2900-3500	58
LED15 SMD E14-CW	08945	E14	6200-6800	58
LED15 SMD E27-WW	08946	E27	2900-3500	72
LED15 SMD E27-CW	08947	E27	6200-6800	72

light distribution / Lichtverteilung
Δ = 120°



220-240V~ 50/60Hz 2,5 2,5 - 22 15 LED SMD 210 120 Ra ≥80 20000 A E I 1/10/100 CE

light source uses SMD 5050 LEDs / das Leuchtmittel verfügt über SMD 5050 LED Dioden

LED24 SMD E14 / E27


LED lamp / LED Lampe



LED24 SMD E14



LED24 SMD E27



Kanlux	Kanlux	LED	Tc [K]	[lm]	[g]	
LED24 SMD E14-WW	18477	3 - 26	E14	2700-3200	270	60
LED24 SMD E14-CW	18476	3 - 28	E14	5700-6300	300	60
LED24 SMD E27-WW	18475	3 - 26	E27	2700-3200	270	74
LED24 SMD E27-CW	18474	3 - 28	E27	5700-6300	300	74

220-240V~ 50/60Hz 3 24 LED SMD 120 Ra ≥75 30000 >15000 A E I 1/10/100 CE

light source uses SMD 5050 LEDs / das Leuchtmittel verfügt über SMD 5050 LED Dioden