



MASTER PL-C 2 Pin

MASTER PL-C 26W/865/2P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Product data

General Information		LLMF 6000 h Rated		LLMF 8000 h Rated	
Cap-Base	G24D-3 [G24d-3]		81 %		77 %
Life To 10% Failures (Nom)	6500 h				
Life To 50% Failures (Nom)	10000 h				
LSF 2000 h Rated	99 %				
LSF 4000 h Rated	98 %				
LSF 6000 h Rated	92 %				
LSF 8000 h Rated	78 %				
Light Technical		Operating and Electrical			
Color Code	865 [CCT of 6500K]	Power (Rated) (Nom)	26.5 W		
Luminous Flux (Nom)	1740 lm	Lamp Current (Nom)	0.335 A		
Luminous Flux (Rated) (Nom)	1740 lm				
Color Designation	Cool Daylight	Temperature			
Chromaticity Coordinate X (Nom)	313	Design Temperature (Nom)	28 °C		
Chromaticity Coordinate Y (Nom)	337				
Correlated Color Temperature (Nom)	6500 K	Controls and Dimming			
Luminous Efficacy (rated) (Nom)	66 lm/W	Dimmable	No		
Color Rendering Index (Nom)	80				
LLMF 2000 h Rated	90 %	Mechanical and Housing			
LLMF 4000 h Rated	85 %	Cap-Base Information	2 Pins		
Approval and Application					
		Energy Efficiency Label (EEL)	B		
		Mercury (Hg) Content (Nom)	1.4 mg		
		Energy Consumption kWh/1000 h	32 kWh		


MASTER PL-C 2 Pin

Product Data

Full product code	871150063531070
Order product name	MASTER PL-C 26W/865/2P 1CT/5X10BOX
EAN/UPC - Product	8711500635310
Order code	927906186540
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	50
Material Nr. (12NC)	927906186540
Net Weight (Piece)	64.300 g
ILCOS Code	FSQ-26/65/1B-I-G24d=3

Dimensional drawing



PL-C 26W/865/2P

Product	D	D1	A	B	C
---------	---	----	---	---	---

