



# MASTER TL5 Circular

## MASTER TL5 Circular 22W/830 1CT/10

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omni-directional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

### Product data

General Information			
Cap-Base	2GX13 [ 2GX13]	Color Rendering Index (Min)	80
Bulb Shape	C-T5 [ C-T5 16 mm]	Color Rendering Index (Nom)	85
Life To 50% Failures Preheat (Nom)	12000 h	LLMF 2000 h Rated	91 %
LSF Preheat 2000 h Rated	99 %	LLMF 4000 h Rated	87 %
LSF Preheat 4000 h Rated	99 %	LLMF 6000 h Rated	84 %
LSF Preheat 8000 h Rated	96 %	LLMF 8000 h Rated	81 %
LSF Preheat 8000 h Rated	89 %	LLMF 12000 h Rated	77 %
LSF Preheat 16000 h Rated	10 %	LLMF 16000 h Rated	74 %
LSF Preheat 20000 h Rated	1 %	LLMF 20000 h Rated	72 %
Light Technical		Operating and Electrical	
Color Code	830 [ CCT of 3000K]	Power (Rated) (Nom)	22.3 W
Luminous Flux (Nom)	1800 lm	Lamp Current (Nom)	0.300 A
Luminous Flux (Rated) (Nom)	1800 lm	Temperature	
Color Designation	Warm White (WW)	Design Temperature (Nom)	35 °C
Chromaticity Coordinate X (Nom)	440	Controls and Dimming	
Chromaticity Coordinate Y (Nom)	403	Dimmable	Yes
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	82 lm/W		
Color Rendering Index (Max)	85		

MASTER TL5 Circular


Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	2.5 mg
Energy Consumption kWh/1000 h	25 kWh
Product Data	
Full product code	871150064095625
Order product name	MASTER TL5 Circular 22W/830 1CT/10
EAN/UPC - Product	8711500640956

Order code	927965083013
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	927965083013
Net Weight (Piece)	80.000 g
ILCOS Code	FSCH-22/30/1B-L/P-2GX13-16

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



TL5-C 22W/830

Product	D	D	E	E	I	I
MASTER TL5 Circular 22W/830 1CT/10	18 mm	14 mm	220 mm	230 mm	187 mm	197 mm

Photometric data

